HK-HD280-(P)(A)-NT

8.0Megapixel H.265 IP Camera

Key Features

X 1/2.7"SC8239 Black light illumination CMOS sensor;1920*1080@25fps

Color 0.0001Lux@F1.2,black/white 0.0001Lux@F1.2

X H.265AI/H.265+(Compatible with H.265/H.264)Support dual stream

AVI;0.1M~8Mpbs variable;1~30f/s variable

- **X** Alarm I/O: 1/0 (support alarm input and video link to background)
- X Supporting human detection and tripping line detection, and supports intelligent functions such as customized face detection, number statistics, etc
- X Support 2D/3D noise reduction, digital wide dynamic



- **X** 2 pcs Black LED, Night Vision Up to 25M
- **% 2.8/4/6/8mm fixed lens**
- **X DC 12V power supply (customizable Poe power supply)**
- **※ IP67**

- **X Support ONVIF; access third party, Support various mobile monitoring (iPhone, Android)**
- ※ Provide web、CMS、center platform management software MYEYE,provide SDK development
- **X** Support cloud technology, easy to achieve network penetration, fro in-line and alarm information pushed

Reasons for choosing

9 upgrade features to meet monitoring needs



Wire supply



Day and night switching



Infrared night vision



30 meters infrared



100-meter transmission



Cell phone remote



Intruder alert



Water and dust proof



Install portable

Infrared night vision

Latest infrared technology

Fill light more uniform infrared night vision without light can see clearly





Frame rate:25

Noise reduction: 3D

Resolution: 1920*1080

Compression Standard:H.265



Super HD Live Demo

Two million ultra-clear shots of the real thing





Camera aging box

Each camera requires a rigorous aging time of more than 24 hours



Warehouse

Product to be released from storage



Suitable for various environment, Wall Mounting & Lifting



Cell phone remote

Multi-terminal support for MOBILE/TABLET/PC Monitor your home from time to time



Multi-focal length optional

Dual seal handling supports waterproof and dustproof

Easy to handle rain and snow weather indoors and outdoors








7M

13M



4M





More features (support for customization)



More products (optional)



Specification

Specifica Model		HK-HD280-(P)(A)-NT
	Image Sensor	1/2.7"SC8239 CMOS ColorVu 24/7 colorful
	DSP	NT98566
	Min. Illumination	Color: 0. 001Lux/F1.2, B/W: 0.0001Lux/F1.2; 0Lux/F1.2(IR on)
li li	Effective Pixels	8MP 3840*2160@15fps; 5MP 2880*1616@25fps
Camera	Scanning System	Progressive
-	Shutter	1/50(1/60)s to 1/10,000s
	Noise reduction	Support 2D/3D
Ī	Wide dynamic	Support digital
1	Max. IR LEDs Length	20-25m (2pcs IR LED)
Camera Features	Day/Night	Auto(ICR)/Color/B/W
	Backlight	BLC / HLC / DWDR
	White Balance	Auto
	Gain Control	Auto/Manual
	Alarm triggered	Motion Detection, occlusion alarm, anomaly
-	SMART event	Perimeter breach detected
	Intelligence analysis	Supporting human detection and tripping line detection
ı	Focal Length	2.8/4/6/8mm fixed lens (Optional)
Lens	Max Aperture	F2.0
Ī	Focus Control	Fixed
\	Video compression	H.265AI/H.265+(Compatible with H.265/H.264), support dual stream, AVI; 0.1M~8Mpbs variable; 1~30f/s variable
	Resolution	1080P(1920*1080) / 720P(1280*720) ; D1(704×576)/ CIF(352×288)
Video	Main Stream	2880*1616@25fps
9	Sub Stream	D1/CIF(1 ~ 25fps)
1	Bit Rate	H.265< H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 20480Kbps
l l	Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTPDHCP/NTP/UPnP etc
[Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, OoS, Boniour
Network	ONVIF	Support
<u> </u>	Max. User Access	10 users
	Smart Phone	iPhone, iPad, Android, Windows Phone
	Client port	VMS/CMS; XMeyey
Auxiliary	Memory Slot	N/A
Interface	Alarm	N/A
,,	Audio	Optional
ļ	Power Supply	DC 12V power supply (customizable Poe power supply)
F	Power Consumption	<8W
General -	Working Environment	-30°C~+60°C, 10%~90%
	Ingress Protection	IP67
ļ	Dimensions	200*200*100mm