



Product Information:

Multilife ECO-S 0W-20

FULLY SYNTHETIC ENGINE OIL

Description

Multilife ECO-S 0W-20 is a high performance fully synthetic engine oil formulated to cope with the exacting demands of OEMs requiring low viscosity engine oils. The product uses a combination of synthetic base fluids and an advanced additive system to provide a balanced lubricant that delivers friction reduction, component protection and fuel efficiency.

Multilife ECO-S 0W-20 provides the following benefits:

- Contributes to overall fuel efficiency
- Circulates rapidly from cold
- Strong oil film protects at high temperatures and under arduous work loads
- Ensures a high level of component cleanliness and operational efficiency

Applications

Recommended for use in engines where a lubricant of this viscosity and performance level is specified in handbooks. Manufacturers include: Honda, Suzuki, Subaru, Toyota, Mazda and Mitsubishi.

Performance Levels

API SN

ILSAC GF-5

GM dexos1

Physical Characteristics

Viscosity @ 100°C, cSt.	8.27
Viscosity @ 40°C, cSt.	46.71
Viscosity Index	166
Density @ 15.5°C	0.850
Flash Point (Closed) °C	205
TBN, mg/KOH/g	7.9
Pour Point °C	-36

Figures based on average production values.

Part No.s: ECS001, ECS005, ECS025, ECS205

(TDS Multilife ECO-S 0W-20 – 110316 issue 6)

