





MODELLO CIMATRICE	LUNGHEZZA TAGLIO (cm)			N° COLTELLI			N° MOTORI	PESO (Kg.)	SPOSTAMENTI IDRAULICI				RETRAIB. TETTO
	A	B	C	A	B	C			LATERALE	ALZATA	INCLINAZ.	INCLINAZ. TETTO	
G800A 	116	50	-	3	1	-	4	181	•	•	•	•	•
	116	78	-	3	2	-	4	189	•	•	•	•	•
	154	50	-	4	1	-	4	191	•	•	•	•	•
	154	78	-	4	2	-	4	199	•	•	•	•	•
	192	50	-	5	1	-	4	201	•	•	•	•	•
	192	78	-	5	2	-	4	209	•	•	•	•	•
G800B 	40	116	50	1	3	1	6	197	•	•	•	•	•
	40	116	78	1	3	2	6	205	•	•	•	•	•
	40	154	50	1	4	1	6	207	•	•	•	•	•
	40	154	78	1	4	2	6	215	•	•	•	•	•
G800C 	40	116	-	1	3	-	4	163	•	•	•	-	-
	40	154	-	1	4	-	4	173	•	•	•	-	-
	40	192	-	1	5	-	4	183	•	•	•	-	-
G800D 	154	-	-	4	-	-	1	157	•	•	•	-	-
	192	-	-	5	-	-	1	167	•	•	•	-	-
	230	-	-	6	-	-	2	177	•	•	•	-	-

Ogni modello della cimatrice “G800” può essere scelto fra 3 versioni diverse a seconda della larghezza di lavoro tra le barre di taglio verticali:

VERSIONE	LARGHEZZA DI LAVORO (Mt.)	
	minimo	Massimo
S	0,90	1,45
N	1,40	1,95
L	1,90	2,60