

Manufacturer: Zaun Limited Web: www.zaun.co.uk Tel: +44 (0)1902 796699 **Product reference:** Spectator Rail with Hockey 200 Height: [\_\_\_\_\_] - 1.0–1.2 m, insert requirements. Gates: Pedestrian: [Not required]. [Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements. Vehicular: [Not required]. [Required]. **Guidance for Hockey 200 Spectator Rail from Zaun Limited** More about Hockey 200 Spectator Rail: As standard As standard Finish: Galvanized and polyester powder coated.

Spectator Rail with Hockey 200 Q40



## Mesh:

Hockey mesh comprising 200 mm of 25 x 50 mm mesh and 200 x 50 mm Duo8 mesh above with single 6 mm vertical wires 50 mm centres and dual 8 mm horizontal wires at 200 mm centres.

## Posts:

60 x 60 mm rectangular hollow section (RHS) posts, spaced at 2525 mm centres.

## Post to panel fixing:

Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 200 mm centres with EPDM inserts. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

## **Gates:**

Framed in 50 x 50 mm RHS, with Zaun Hockey 200 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.