

Standard Cup Pigs

Designed for cleaning, batching and gauging, IK-UK's cup pig is a universally popular style of pig. The cup design is derived from the hydraulic piston seal and aggressively scrapes the pipeline bore while maintaining a good seal.

The range is comprehensive 2" through to 56" with 2, 3 or 4 cup models and a variety of body constructions available.

In sizes 2" up to 14" a spindle (bolt) body can be offered or alternatively, the complete range up to 56" can be supplied as a multi bolt design.



Conical Cup Pigs

These pigs are especially suitable when encountering pipe ovality and varying pipe wall thickness. Designed for cleaning, batching and gauging, IK-UK's conical cup pigs allow maximum flexibility while maintaining a positive seal.

The range is comprehensive 2" through to 48" with 2, 3 or 4 cup models and a variety of body constructions available.

In sizes 2" up to 14" a spindle (bolt) body can be offered or alternatively the complete range up to 48" can be supplied as a multi bolt design.

Other design options include the attachment of gauging plates, cleaning brushes, transmitter housings and magnets (for debris collection).

- As standard all IK-UK's pigs are designed to pass minimum 3D radius bends and negotiate full bore branches.
- Optional polyurethane bumper noses available.
- All multi bolt pig body assemblies are welded to code standard BS EN ISO 15614-1:2004+A1:2008.
- NDT testing (MPI) of the welds can be performed if requested.
- All pipeline mediums can be accommodated
- For Sour Service (H₂S) IK-UK offers polyurethane coating of all carbon steel components
- Can be fitted with Online Electronics tracking equipment