

TRIO

NTM  
www.ntm.fi

# NTM

**FUTURE  
NOW!**



*Easy as  
One, Two, Three*

TRIO-3-chamber rear loader

www.ntm.fi

## TRIO - Technical Specifications

TRIO recycling vehicle features three compartments. TRIO is ideal for conditions with limited space, as all three sections are emptied through the back of the vehicle.

TRIO supports independent compression of each cell as the waste material rests inside the vehicle. Automatic bin grip is offered as standard equipment, with each cell being gripped and handled separately. The cells are emptied simultaneously.

When the refuse collection vehicle itself is emptied each section is processed one at a time. There are three separate emptying bases to ensure convenient and secure waste removal, without risk of mixing the various waste materials. TRIO emptying bases can be emptied in any order.

TRIO can easily be adjusted to fit a variety of chassis.

Load volume (net)	18-25 m <sup>3</sup>
Body weight including bin lift	7900 - 9100 kg
Height above chassis frame	2750 mm
Width	2550 mm
Total length	8200 - 9500 mm
Work cycle	10 s
Lifting capacity	510 kg (3 x 170 kg)
Bin sizes	(120) 140 - 370 l

### Standard equipment:

- Bin lift
- Pneumatic allocation bar
- Automatic bin grip
- Inspection windows
- Rotating warning light
- Vehicle work lights
- Mud guards, mud flaps
- Camera with in cab monitor for loading and reversing
- Prepared for frame scale

### Optional:

- Weighing equipment for bin lift
- Hydraulic oil heater
- Auto lube
- Modem for PLC system



The manufacturer reserves the right to make alterations without prior notice.