

Health and Safety Information

Elastomeric Bitumen Sealant

1 Product and Company

1.1 Identification of the substance or preparation:

Product name: Elastomeric Bitumen Sealant 0751/0785

1.2 Use of the substance or the preparation: Sealant

1.3 Company/undertaking identification:

Adawall Ltd

Registered No 11056982

Garner Street Business Park, Garner Street, Etruria, Stoke-On-Trent, ST4 7BH

www.adawall.co.uk

1.4 Telephone number for emergency:

08452 238 801

2 Composition

Hazardous ingredients	CAS No.	Conc in %.	Hazard	Risks
	EINECS No	in %	symbol	(R-phrases)
Naptha,hydrodesulfurized	64742-82-1	2.5 - <25	F;Xn;N	11-51/53-65-67
Heavy (Conc benzene <0.1%)	265-185-4			
Asphaltbitumes	8052-42-4	>25	-	-
	232-490-9			
quaternary ammonium	8030-78-2			
compounds, trimethyltallow	232-447-4	1 - <5	F;C	11-22-34
alkyl, chlorides				

3 Hazards Identification

- Flammable

- Harmful to aquatic organisms; may cause long-term adverse effects in the aquatic environment

4 First aid Measures

4.1 Eye contact:

- Rinse immediately with plenty of water
- Seek medical advice

4.2 Skin contact:

- Rinse immediately with plenty of water
- If irritation persists: seek medical advice

4.3 After inhalation:

- Remove the victim into fresh air
- Seek medical advice

4.4 After ingestion:

- Never give water to an unconscious person
- Do not induce vomiting
- Seek medical advice

5 Fire Fighting Measures

5.1 Suitable extinguishing media:

- Water spray
- Polyvalent foam
- Dry chemical powder, Carbon Dioxide.

5.2 Unsuitable extinguishing media:

- Solid water jet ineffective as extinguishing medium

5.3 Special exposure hazards:

- On burning: release of carbon monoxide and carbon dioxide
- Gas/vapour flammable with air within explosion limits

5.4 Instructions:

- Take account of toxic firefighting water
- Use firefighting water moderately and contain it

5.5 Special protective equipment for firefighters:

- Heat/fire exposure: compressed air/oxygen apparatus

6 Accidental release measures

6.1 Personal protection/precautions:

see heading 8.1/8.3/10.3

6.2 Environmental precautions:

- Use appropriate containment to avoid environmental contamination

6.3 Methods of cleaning up:

- Take up liquid spill into inert absorbent material e.g.: sand/earth
- Take collected spill to competent authority
- Wash clothing and equipment after handling

7 Handling and Storage.

7.1 Handling:

- Observe strict hygiene
- Avoid prolonged and repeated contact with skin
- In case of insufficient ventilation: keep naked flames/sparks away
- Do not discharge the waste into the drain
- Remove contaminated clothing immediately

7.2 Storage:

- Keep container tightly closed
- Keep away from: heat sources, ignition sources

Storage temperature : Room temperature

Quantity limits : N.D. kg

Storage life : 365 days

8 Exposure/Personal Protection

8.1 Exposure limit values:

ASPHALTBITUMES:

TLV-TWA : 0.5 l mg/m³ - ppm

TLV-STEL : - mg/m³ - ppm

TLV-Ceiling : - mg/m³ - ppm

OES-LTEL : 5 fumes mg/m³ - ppm

OES-STEL : 10 fumes mg/m³ - ppm

MAK : - mg/m³ - ppm

TRK : 10 E mg/m³ - ppm

MAC-TGG 8 h : 5 rook mg/m³

MAC-TGG 15 min. : - mg/m³

MAC-Ceiling : - mg/m³

VME-8 h : - mg/m³ - ppm

VLE-15 min. : - mg/m³ – ppm

GWBB-8 h : 5 rook mg/m³ - ppm

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Use only in well ventilated area

8.2.2 Environmental exposure controls: see heading 13

8.3 Personal protection:

8.3.1 respiratory protection:

- In case of insufficient ventilation: respiratory protection with filter type A

8.3.2 hand protection:

- Chemically resistant gloves

8.3.3 eye protection:

- Safety glasses

8.3.4 skin protection:

- Suitable protective clothing

9 Physical and Chemical properties

9.1 General information:

Appearance (at 20°C) : Viscous

Odour : Naphtha

Colour : Black

9.2 Important health, safety and environmental information:

pH value : N.D.

Boiling point/boiling range : 160 °C

Flashpoint : 44 °C

Explosion limits : N.D. Vol%

Vapour pressure (at 20°C) : 6 hPa

Vapour pressure (at 50°C) : N.D. hPa

Relative density (at 20°C) : 1.3

Water solubility : Insoluble

Soluble in : Aromatic hydrocarbons, aliphatic hydrocarbons

Relative vapour density : N.D.

Viscosity (at 20°C) : 78 Pa.s

Flow time (according to ISO 2431) : > 60 s

Partition coefficient n-octanol/water : N.D.

Evaporation rate

ratio to butyl acetate : N.D.

ratio to ether : N.D.

9.3 Other information:

Melting point/melting range : N.D. °C

Auto-ignition point : 210 °C

Saturation concentration : N.D. g/m³

I0 Stability and reactivity

I0.1 Conditions to avoid/reactivity:

- Stable under normal conditions

I0.2 Materials to avoid:

- Keep away from: heat sources, ignition sources

I0.3 Hazardous decomposition products:

- On burning: release of carbon monoxide and carbon dioxide

I1 Toxicological Information

I1.1 Acute toxicity:

LD50 oral rat : N.D. mg/kg

LD50 dermal rabbit : N.D. mg/kg

LD50 dermal rabbit : N.D. mg/kg

LC50 inhalation rat : N.D. mg/l/4 h

LC50 inhalation rat : N.D. ppm/4 h

I1.2 Chronic toxicity:

EC carc. cat. : not listed

EC muta. cat. : not listed

EC repr. cat. : not listed

Carcinogenicity (TLV) : not listed

Carcinogenicity (MAC) : not listed

Carcinogenicity (VME) : not listed

Carcinogenicity (GWBB) : not listed

Carcinogenicity (MAK) : not listed

Mutagenicity (MAK) : not listed

Teratogenicity (MAK) : not listed

IARC classification : not listed

I1.3 Routes of exposure: ingestion, inhalation, eye and skin

I1.4 Acute effects/symptoms:

AFTER INHALATION:

EXPOSURE TO HIGH CONCENTRATIONS:

- Feeling of weakness
- Dizziness
- Headache
- Nausea
- Disturbances of consciousness

AFTER INGESTION:

- Nausea
- Irritation of the gastric/intestinal mucosa

AFTER EYE CONTACT:

- Slight irritation

ON CONTINUOUS EXPOSURE/CONTACT:

- Irritation of the eye tissue

11.5 Chronic effects:

ON CONTINUOUS EXPOSURE/CONTACT:

- Dry skin
- Skin rash/inflammation

12 Ecological Information

12.1 Ecotoxicity:

- No data available

12.2 Mobility:

- **Volatile organic compounds (VOC):** 15 %
- Insoluble in water
- Substance sinks in water

For other physicochemical properties see section 9

12.3 Persistence and degradability:

- **Biodegradation BOD5** : N.D. % ThOD

- **water** : No data available

- **soil** : T ½ N.D. days

12.4 Bioaccumulative potential:

- **log Pow** : N.D.

- **BCF** : N.D.

12.5 Other adverse effects:

- **WGK** : 2 (classification based on the components in compliance

with Verwaltungsvorschrift wassergefährdender Stoffe

(VwVwS) of 17 May 1999)

- **Effect on the ozone layer** : Not dangerous for the ozone

layer (1999/45/EC)

- **Greenhouse effect** : No data available

- **Effect on waste water purification** : No data available

13 Disposal Considerations

13.1 Provisions relating to waste:

- Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of

16/2/2001): 08 04 09* (waste adhesives and sealants containing organic

solvents or other dangerous substances)

- Hazardous waste (91/689/EEC)

13.2 Disposal methods:

- Incinerate under surveillance

- Substance must not be discharged into the sewer

- Do not discharge into surface water

13.3 Packaging:

- Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC,

O.J. L47 of 16/2/2001): 15 01 10* (packaging containing residues of or contaminated by dangerous substances)

I4 Transport Information

I4.1 Classification of the substance in compliance with UN Recommendations

UN number : -

CLASS : NOT SUBJECT

SUB RISKS :

PACKING :

PROPER SHIPPING NAME :

UN 3295, Hydrocarbons, liquid, n.o.s.(naphtha, hydrodesulfurized heavy)

I4.2 ADR (transport by road)

CLASS : NOT SUBJECT

PACKING :

DANGER LABEL TANKS :

DANGER LABEL PACKAGES :

I4.3 RID (transport by rail)

CLASS : NOT SUBJECT

PACKING :

DANGER LABEL TANKS :

DANGER LABEL PACKAGES :

I4.4 ADNR (transport by inland waterways)

CLASS : NOT SUBJECT

PACKING :

DANGER LABEL TANKS :

DANGER LABEL PACKAGES :

I4.5 IMDG (maritime transport)

CLASS : 3

SUB RISKS :

PACKING : III

EMS : F-E, S-E

MARINE POLLUTANT : -

I4.6 ICAO (air transport) :

CLASS : 3

SUB RISKS : -

PACKING : III

PACKING INSTRUCTIONS PASSENGER AIRCRAFT : 309/Y309

PACKING INSTRUCTIONS CARGO AIRCRAFT : 310

I4.7 Special precautions in connection with transport:

Viscous liquid with a flash point ranging from 23°C to 61°C, which meets the conditions indicated in 2.3.3.1.5 of ADR, RID and ADNR and in 2.3.2.5 of IMDG not subject to ADR, RID and ADNR and neither to IMDG Code chapters 4.1, 5.2, 6.1

I5 Regulatory Information

Labelling in accordance with EC directives 67/548/EEC and 1999/45/EC

R10 : Flammable

R52/53 : Harmful to aquatic organisms; may cause long-term adverse effects in the aquatic environment

S(02) : (Keep out of reach of children)

S61 : Avoid release to the environment. Refer to special instructions/safety data sheets.

I6 Other Information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE

N.D. = NOT DETERMINED

* = INTERNAL CLASSIFICATION

Exposure limits:

TLV : Threshold Limit Value - ACGIH US 2002

OES : Occupational Exposure Standards - United Kingdom 2001

MEL : Maximum Exposure Limits - United Kingdom 2001

MAK : Maximale Arbeitsplatzkonzentrationen - Germany 2001

TRK : Technische Richtkonzentrationen - Germany 2001

MAC : Maximale aanvaarde concentratie - the Netherlands 2002

VME : Valeurs limites de Moyenne d'Exposition - France 1999

VLE : Valeurs limites d'Exposition à court terme - France 1999

GWBB : Grenswaarde beroepsmatige blootstelling - Belgium 2002

GWK : Grenswaarde kortstondige blootstelling - Belgium 2002

EC : Indicative occupational exposure limit values - directive 2000/39/EC

I : Inhalable fraction = **T** : Total dust = **E** : Einatembarer Aerosolanteil

R : Respirable fraction = **A** : Alveolengängiger Aerosolanteil/Alveolar dust

C : Ceiling limit

a: aerosol **r**: rook/Rauch (fume)

d: damp (vapour) **st**: stof/Staub (dust)

du: dust **ve**: vezel (fibre)

fa: Faser (fibre) **va**: vapour

fi: fibre **om**: oil mist

fu: fume **on**: olienevel/Ölnebel (oil mist)

p: poussière (dust) **part**: particles

Chronic toxicity:

K : List of the carcinogenic substances and processes - The Netherlands 2002

Full text of any R-phrases referred to under heading 2:

R11 : Highly flammable

R22 : Harmful if swallowed

R34 : Causes burns

R51/53 : Toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment

R65 : Harmful: may cause lung damage if swallowed

R67 : Vapours may cause drowsiness and dizziness