

SOLOCHILL[®]

M I C R O D I S T R I B U T E D

AVAILABLE CASES

	Display Case		Lengths				Doors							
			4'	6'	8'	10'	12'	1	2	3	4	5	6	
Reach-In Low-Temp	ORZQA	VA					R*	✓	✓	✓	✓	✓	✓	
	ORZHQA	VA					R*	✓	✓	✓	✓	✓	✓	
	ONRZQA	VA					R*	✓	✓	✓	✓	✓	✓	
	ONRZHQA	VA					R*	✓	✓	✓	✓	✓	✓	
	VNRZQA	VA					R*	✓	✓	✓	✓	✓	✓	
	VNRZHQA	VA					R*	✓	✓	✓	✓	✓	✓	
Reach-In Medium-Temp	ORBQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	
	ORBHQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	
	ONRBQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	
	ONRBHQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	
	VRBQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	
	VRBHQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	
	VNRBQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	
	VNRBHQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	
Utility	DLPC	IA	R*	✓*	✓*	✓*	✓*							
	KFD (Slave/Secondary Only) (No master)	IA	R*	R*	R*	R*	R*							
	NFD	IA	R*	✓*	✓*	✓*								
	NFT	IA	R*	^*	^*	^*								
	NFO	IA	R*	✓*	✓*	✓*								
	O3UMQA	VA			R*							R*		
	O4UMQA	VA			R*							R*		
	O25UMQA	VA			R*							R*		
	O35UMQA	VA			R*							R*		
	O325UMQA	VA			R*							R*		
	ON2UMQA	VA			R*							R*		
	ON3UMQA	VA			R*							R*		
	ON4UMQA	VA			R*							R*		
	ON5UMQA	VA			R*									
	ON35UMQA	VA			R*							R*		
	O3UDQA	VA			R*							R*		
	OMQA	VA			R*							R*		
	ON3EMQA	VA	R*											
	PC-G-R	IA	R*	✓*	✓*	✓*	✓*							
	Multi-Deck	BLF-SR	IA	R*	^*	^*								
		DLPF	IA	R*	✓*	✓*	✓*	✓*						
		FT	IA	R*	^*	^*	^*	^*						
		O5MQA	VA	✓	✓	✓							✓	
O5MHQA		VA	✓	✓	✓							✓		
O5DMQA		VA	✓	✓	✓	✓	✓					✓		
O5DMHQA		VA	✓	✓	✓	✓	✓					✓		
ON5DMXQA		VA	✓	✓	✓	✓	✓					✓		
ON5DMHXQA		VA	✓*	✓*	✓							✓		
ON5MHXQA		VA	✓*	✓*	✓							✓		
OHPQA		VA	✓	✓	✓							✓		
OHPHQA		VA	✓	✓	✓							✓		
OHMQA		VA	✓	✓	✓							✓		
OHHMQA		VA	✓	✓	✓							✓		
6DMLHQA		VA	✓	✓	✓							✓		
6MLHQA		VA	✓		✓							✓	✓	
6NDMLHQA		VA			✓							✓		
PF - 48", 51", 54", 72"		IA	R*	^*	^*	^*	^*							
QC		IA	R*	✓*	✓*	✓*	✓*							

	Case Model		Lengths				
			4'	6'	8'	10'	12'
Islands Low-Temp	OWIZVQA	VA	R*	R*	R*	R*	R*
	OWEZVQA	VA		R*			
	ONIZGGQA	VA			R*		R*
	OWZGGQA	VA		R*	R*	R*	R*
	OEZVQA	VA	R*				
Islands Medium-Temp	i2i (Ft length notes length of center section)	IA	✓*	✓*	✓*	✓*	✓*
	OIP(B/BB)QA	VA			R*		R*
	O3IM(B)QA	VA			R*		R*
	O4ID(B)QA	VA			R*		R*
	PFI (Ft length notes length of center section)	IA	✓*	✓*	✓*	✓*	✓*
Service	AGB	IA	R*	✓*	✓*		
	BLF-R	IA	R*	^*	^*		
	BMD-R	IA	R*	^*	^*	^*	^*
	BMD-RG	IA	R*	^+*	^+*	^+*	^+*
	BSD-SW	IA	R>*	^>*	^>*	^>*	^>*
	GMD-R	IA	R*	✓*	✓*	✓*	✓*
	GMD-RG	IA	R+*	^+*	+*	+*	+*
	GMD-RGC / SSC	IA		#^*	#*	#*	#*
	GSD-R	IA	R*	^*	✓*	✓*	✓*
	SMD-R	IA	R*	^>*	✓*	✓*	✓*
	SMD-RG	IA	R*	^+*	+*	+*	+*
	SSD-R	IA	R*	^*	✓*	✓*	✓*
	SSD-R-LT	IA	R*	^*			
	SSGC	IA		R#*	#*	#*	#*
	S2SGC	IA		R#*	#*	#*	#*
	S2SG	IA	R>*	R>*	R*	R*	R*
	S2SB	IA	R>*	R>*	R*	R*	R*
	SSA	IA	R>*	R>*	R*	R*	R*
	SSAW	IA	R>*	R>*	R*	R*	R*
	SSA-RG	IA	R>*	R>*	R*	R*	R*
	SSM	IA	R>*	R>*	R*	R*	R*
	SSAM-RG	IA	R>*	R>*	R>*	R>*	R*
	SSAS-RG	IA	R>*	R*	R*	R*	R*
SSF	IA	R>*	R>*	R>*	R*	R*	
SSF-RG	IA	R>*	R>*	R*	R*	R*	
SSFM - RG	IA	R>*	R*	R*	R*	R*	
SSFS - RG	IA	R>*	R*	R*	R*	R*	
SGM	IA	R>*	R>*	R>*	R*	R*	
Combo	PT	IA	R*	^*	^*	^*	^*
	PTD-R	IA	R*	^*	^*	^*	^*
	PTD-RG	IA	R*	^+*	^+*	^+*	^+*
	PTD-RGC / SSC	IA		R#*	^#*	^#*	^#*
	PTD-GSD	IA	R*	^*	^*	^*	^*
	SD-RG	IA	R*	^+*	^+*	^+*	^+*
	SD	IA	R*	^*	^*	^*	^*
	DB	IA	R*	^*	^*	^*	^*
	BLF-CR	IA	R*	^*	^*	^*	^*
	Food Bar	CWC	IA	R*	^>*	^>*	^>*
SB		IA	R*	^>*	^>*	^>*	^>*
SBI		IA	R*	^>*	^>*	^>*	^>*

KEY

- ✓ = 12 week lead-time.
- * = 16 week lead-time.
- R = Remote located SoloChill unit or a slave configuration.
- + = Must go with gravity refrigeration models.
- I = Only available with R410A refrigerant.
- > = Requires it to be part of a master slave line up.
- ^ = Mark notes design modifications to accept master.
- # = Master only.
- IA= Specialty products manufactured in Iowa.
- VA= Case products manufactured in Virginia.

SOLOCHILL[®]
MICRO DISTRIBUTED

Hillphoenix
a  company