

TENAX TRACKWAY

Extruded net

TENAX TRACKWAY is an extruded PE panel mesh used to protect green areas from the passage of heavy construction vehicles. Its thickness and wide mesh protect the wheels from mud increasing the grip.

Typical applications:

- Heavy vehicles passageways
- Mud areas
- Gravel containment
- Dirt road reinforcement

PHYSICAL CHARACTERISTICS	TEST METHOD	UNIT	TRACKWAY	NOTES
COMPOSITION			FOAM POLYETHYLENE	-
STRUCTURE			RHOMBOIDAL	-
COLOUR			BLACK	-
PACKAGING			-	-

DIMENSIONAL CHARACTERISTICS	TEST METHOD	UNIT	TRACKWAY	NOTES
UNIT WEIGHT		g/m ²	4000	-
PIECE WIDTH		m	2.05	-
PIECE LENGTH		m	1.20	-
COVERED AREA		m ²	2.46	-
PIECE VOLUME		m ³	0.08	-
PIECE WEIGHT		Kg	9.9	-





Just indicating

The data contained in this publication are based on the knowledge available at the time of printing and may be subjected to amendments due to changes of the methods of testing and/or manufacturing. All dimensions and properties are reported as typical values. Tenax nets are thermoplastic products subjected to shrinkage. MD: longitudinal direction. TD: transversal direction.



TENAX Spa Quality System has been assessed and registered in agreement with ISO:9001:2008 by SGS Italy and SGS UK.

The TENAX Laboratory has been operational in 1980 and has been continuously improved with the purpose of assuring unequalled technical development of the products and accurate Quality Control.

The TENAX Laboratory can perform mechanical, hydraulic and durability tests, according to the most important international standards like ISO, CEN, ASTM, DIN, BSI, UNI.



TENAX SpA
Via dell'Industria, 3
23897 Viganò (LC)
Tel. +39 039.9219300
Fax +39 039.9219290
customer.service@tenax.net