(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2 Revision date: 31/07/2013 a geos www.algeos.com

Page 1 of 10 Print date: 31/07/2013

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: OrthaBond

1.2 Relevant identified uses of the mixture and uses advised against.

Not recommended for domestic use

1.3 Details of the supplier of the safety data sheet.

Company: Address:	A. Algeo Ltd. Sheridan House, Bridge Industrial Estate, Speke Hall Road, Liverpool L24 9HB
Telephone:	+44 (0)151 448 1228
Fax:	+44 (0)151 448 1008
E-mail:	sales@algeos.com

1.4 Emergency telephone number: +44 (0)151 448 1228 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Directive 1999/45/EC: F Xi N Highly flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. In accordance with Regulation (EU) No 1272/2008: Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects. Eye Irrit. 2 : Causes serious eye irritation. Skin Irrit. 2 : Causes skin irritation. STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Warning

H statements:

(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2 Revision date: 31/07/2013



Page 2 of 10 Print date: 31/07/2013

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

P statements:

P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P501	Dispose of contents/container to
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P305+P351+P present and ea	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if isy to do. Continue rinsing.

EUH statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains: hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6)) cyclohexane butanone,ethyl methyl ketone ethyl acetate

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Mixtures.

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classificatio n Regulation (EC) No 1272/2008	(*)Classificatio n Directive 67/548/CEE
Index No:601-007-00-7 CAS NO: N. CE: Registration No:01- 2119484651-34-XXXX	(**) hexane, mixture of isomers (containing < 5 % n-hexane (203-777-6))	2.5 - 25 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Skin Irrit. 2, H315 - STOT SE 3, H336	F N Xi R11 R51/53 R67 R38
Index No:601-017-00-1 CAS NO:110-82-7 N. CE:203-806-2 Registration No:01- 2119463273-41-XXXX	(**) cyclohexane	2.5 - 25 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Skin Irrit. 2, H315 - STOT SE 3, H336	F Xi N R11 R38 R67 R50/53

(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2 Revision date: 31/07/2013



Page 3 of 10 Print date: 31/07/2013

Index No:606-002-00-3 CAS NO:78-93-3 N. CE:201-159-0 Registration No:01- 2119457290-43-XXXX	(**) butanone,ethyl methyl ketone	2.5 - 15 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	F Xi R11 R36 R66 R67
Index No:607-022-00-5 CAS NO:141-78-6 N. CE:205-500-4 Registration No:01- 2119475103-46-XXXX	(**) ethyl acetate	20 - 25 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	F Xi R11 R36 R66 R67

(*) The complete text of the R and H phrases is given in section 16 of this Safety Data Sheet.

(**) Substance with a Community workplace exposure limit (see section 8.1).

4. FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO_2 . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture. Special risks.

(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2 Revision date: 31/07/2013



Page 4 of 10 Print date: 31/07/2013

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. Avoid breathing fumes.For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product Dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation.Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate de-contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

7.3 Specific end use(s).

See tecnical data sheet

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2 Revision date: 31/07/2013



Page 5 of 10 Print date: 31/07/2013

8.1 Control parameters.

Work exposure limit for:

	VLA-	ED *	VLA-EC *		
Name	ppm	mg/m ³	ppm	mg/m ³	
hexane, mixture of isomers (containing < 5 % n-hexane (203- 777-6))	500	1790	1000	3580	
cyclohexane	200	700			
butanone, ethyl methyl ketone	200	600	300	900	
ethyl acetate	400	1460			

* According to the list of Limit Environmental Professional Exposure Values adopted by the National Institute for Safety and Hygiene at Work for the year 2012.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Breathing protection:

<u>PPE:</u> Filter mask for protection against gases and particles. <u>Characteristics:</u> «CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight. <u>CEN standards:</u> EN 136, EN 140, EN 405



<u>Maintenance</u>: Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. <u>Observations</u>: Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.

Hand protection:

<u>PPE:</u> Protective gloves against chemicals. <u>Characteristics:</u> «CE» marking, category III. <u>CEN standards:</u> EN 374-1, En 374-2, EN 374-3, EN 420



<u>Maintenance:</u> Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. <u>Observations:</u> Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.

Protective creams can help to protect exposed areas of the skin. These creams must **NEVER** be applied once exposure has occurred.

Eye protection:

(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2 Revision date: 31/07/2013



Page 6 of 10 Print date: 31/07/2013

<u>PPE:</u> Protective goggles with built-in frame. <u>Characteristics:</u> «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour. <u>CEN standards:</u> EN 165, EN 166, EN 167, EN 168



<u>Maintenance</u>: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. <u>Observations</u>: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.

Skin protection:

<u>PPE:</u> Anti-static protective clothing. <u>Characteristics:</u> «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. <u>CEN standards:</u> EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5



<u>Maintenance</u>: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.

<u>Observations</u>: The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.

<u>PPE:</u> Anti-static safety footwear. <u>Characteristics:</u> «CE» marking, category II. <u>CEN standards:</u> EN ISO 13287, EN ISO 20344, EN ISO 20346



Maintenance: The footwear should be checked regularly

<u>Observations</u>: The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance:N.A./N.A. Odour:N.A./N.A. Odour threshold:N.A./N.A. pH:N.A./N.A. Melting point:N.A./N.A. Boiling Point: N.A./N.A. Flash point: -16 °C Evaporation velocity: N.A./N.A. Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: 1 Upper Explosive Limit: 12.8 Vapour pressure: N.A./N.A. Vapour density:2.9 Relative density:0.81 gr/cm³ Solubility:N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A. Partition coefficient (n-octanol/water): N.A./N.A. Auto-ignition temperature: 514°C Decomposition temperature: N.A./N.A. Viscosity: 1000-2500 Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2

Revision date: 31/07/2013



Page 7 of 10 Print date: 31/07/2013

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2. Other information.

VOC content (p/p): 77,271 % VOC content: **625,897** g/l

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

No information is available regarding the toxicity of the substances present.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
		Log Pow	BCF	NOECs	Level
butanone, ethyl methyl ke	tone	0,29			Von / High
N. CAS: 78-93-3	N. CE: 201-159-0	0,29			Very High
ethyl acetate		0,73			Von/ High
N. CAS: 141-78-6	N. CE: 205-500-4	0,75			Very High

(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2 Revision date: 31/07/2013



Page 8 of 10 Print date: 31/07/2013

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport. Land: Transport by road: ADR, Transport by rail: RID. Transport documentation: Consignment note and written instructions Sea: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number.

UN No: UN1133

14.2 UN proper shipping name. Description: UN 1133 ADHESIVES, 3, PG II, (D/E), ENVIRONMENTALLY HAZARDOUS

14.3 Transport hazard class(es). Class(es): 3

14.4 Packing group. Packing group: II

14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

14.6 Special precautions for user. Labels: 3

(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2 Revision date: 31/07/2013



Page 9 of 10 Print date: 31/07/2013



Hazard number: 33 ADR LQ: 5 L

Transport by ship, FEm - Emergency sheets (F - Fire, S - Spills): F-E,S-D Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

See annex I of the Directive 96/82/EC of 9 December 1996 on the control of major-accident hazards involving dangerous substances and the Regulation (EC) No 689/2008 of the european parliament and of the council of 17 June 2008 concerning the export and import of dangerous chemicals and its subsequent updates.

15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

SECTION 16: OTHER INFORMATION.

Complete text of the R phrases that appear in section 3:

R11	Highly flammable.
R36	Irritating to eyes.
R38	Irritating to skin.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Sections changed compared with the previous version:

1,3,8,11,12,15,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Labelling in accordance with Directive 1999/45/EC:

(in accordance with Regulation (EC) No 1907/2006)

OrthaBond

Version: 2 Revision date: 31/07/2013



Page 10 of 10 Print date: 31/07/2013

Symbols:



Irritant



R Phrases: Highly flammable. R11 Repeated exposure may cause skin dryness or cracking. R66 R67 Vapours may cause drowsiness and dizziness. R36/38 Irritating to eyes and skin. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. S Phrases: Keep container in a well-ventilated place. S9 S16 Keep away from sources of ignition - No smoking. Avoid contact with skin. S24 S33 Take precautionary measures against static discharges. Use only in well-ventilated areas. S51 Use appropriate container to avoid environmental contamination. S57 S61 Avoid release to the environment. Refer to special instructions/safety data sheets. The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU)

No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.