



Down flow model

Ventilated Workstation - Wall Location

Removable perforated cover panels located over extract sump. Air is drawn down evenly across the entire ventilated work area.



Sump wash down, controlled by this remote manually operated valve.

All components are fabricated from quality stainless steel with 'Supersilk' satin polished finish.

Full self supporting stainless steel under structure. Adjustable height options also available.

Model shown is 1500 Downflow Ventilated Workstation 750mm wide with integrally formed sink, lever action mixer, trigger operated wash hose and remote sump wash down valve.

DESIGNS:	Constant Air Volume
MODELS:	Down flow or Cross flow extract
CONSTRUCTION:	Heavy gauge stainless steel
FINISH:	'Supersilk' satin polish, all components
WORK SURFACE:	One piece, 16swg, 316 stainless steel
SUMP AREA:	Integrally formed, 16swg, 316 stainless steel
SINK:	Integrally formed, 16swg, 316 stainless steel
WASTE OUTLETS:	Integrally formed, 18swg, 316 stainless steel
AIR VELOCITY:	0.40 m/sec, average over ventilated work area
STATIC PRESSURE	120 Pascals over standard table (including
LOSS:	extract manifold)
PLUMBING:	Factory pre-plumbed, tested & certified
WATER PRESSURE:	Incoming supplies not to exceed 10 bar
DIMENSIONS:	* 1200mm, 1500mm, 1800mm, 2000mm long
TYPICAL VOLUME:	1200 = 0.13 m3/sec 1500 = 0.20 m3/sec
	1800 = 0.26 m3/sec 2000 = 0.31 m3/sec
	Based on arrangement as pictured above.
EXTRACT:	Flanged or slip joint connection to suit site.

OPTIONS:

- Electrically operated height adjustment (See separate Data Sheet)
- Manufactured in any modular size up to 2500mm long.
- Cross flow extract.
- Flexible or rigid copper internal plumbing.
- Airflow monitor.
- Stainless steel or PVC extract connections.



