

## DAMAR ULTRAX

### Description

A speciality high performance solventborne line-marking paint, possessing excellent drying, very good glass bead retention and good wear resistance properties.

Available: 20 litre, 200 litre, 1000 litre.

### Typical Uses

- For line marking on all common roading surfaces.
- For road-marking where glass beads and holdfix is required.

### Properties

<b>Resin System</b>	Alkyd
<b>Pigmentation</b>	Titanium Dioxide
<b>Finish</b>	Matt
<b>Colour</b>	White
<b>Dilution Rate</b>	Use as supplied.
<b>Theoretical Coverage</b>	d.f.t. 2.5M2 @ 240mic d.f.t.
<b>Dry Time @ 25°C</b>	<7 minutes rapid dry
<b>Number of Coats</b>	1
<b>Clean Up</b>	Thinners PF4 or Toluene
<b>Volume Solids</b>	60.0% ± 2%

### Performance / Limitations

- Fast drying and excellent adhesion to aged roadmarking paint.
- Excellent resistance to bleeding of bitumen.
- NOT recommended for damp or wet surfaces. Ensure temperature is over 10° C.
- Suitable for intermix or standard drop-on beads.

- Application to concrete is problematic due to large variations in drying agents and surface finishes available, plus surface contaminations.
- For application to concrete surfaces please refer to concrete application sheet

### Preparation

- Surfaces must be clean, dry, free from oil, grease, lichen, etc before application.
- Can be applied to bare, unprimed or unsealed bitumen based surfaces\*

\*For concrete painting see concrete preparation information sheet

### Application

- Airless Spray: Thinning is normally not required, but for ease of application product can be thinned up to 5% (v/v) with Toluene when spraying.
- Stir thoroughly before use.

### Approvals

New Zealand NZTA M/7 2017 CNO\* AE1\*

\*M7 approvals based on an application rate of 220 microns DFT (Dry Film Thickness)

### Health and Safety

- For detailed information refer to the Material Safety Data Sheet and label for this product.
- Provide adequate ventilation during use.
- Avoid breathing vapour.
- Wear eye protection when handling as splashes to the eye may cause irritation.
- If swallowed or eyes become contaminated, seek immediate medical attention.
- Product is FLAMMABLE.
- DO NOT smoke in work area.
- Handle with care.