Auto Klene Acid Klene WA

Auto Klene Solutions Chemwatch: 5240-43A Version No: 2.1.1.1

Safety Data Sheet according to HSNO Regulations

Chemwatch Hazard Alert Code: 4

Issue Date: **26/01/2017**Print Date: **08/02/2017**S.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier			
Product name	Auto Klene Acid Klene WA		
Synonyms	Aluminium Cleaner/Brightener. Wheel Cleaner.		
Proper shipping name	AMMONIUM HYDROGEN- DIFLUORIDE SOLUTION		
Other means of identification	Not Available		
Relevant identified uses of the substance or mixture and uses advised against			
Relevant identified uses	Aluminium Cleaning/Brightening. Wheel cleaner.		

GHS label elements







SIGNAL WORD

DANGER

Hazard statement(s)

Chemwatch: **5240-43**Version No: **2.1.1.1**

Issue Date: 26/01/2017
Print Date: 08/02/2017

H290 May be corrosive to metals. Registered company name Address 1/83 Merrindale Drive VIC Croydon 3136 Australia Telephone +61 3 8761 1900 Fax +661 3 8761 1955 Website https://www.autoklene.com/msds/
Registered company name Auto Klene Solutions 1/83 Merrindale Drive VIC Croydon 3136 Australia Telephone +61 3 8761 1900 Fax +61 3 8761 1955 Website https://www.autoklene.com/msds/
Registered company name Auto Klene Solutions 1/83 Merrindale Drive VIC Croydon 3136 Australia Telephone +61 3 8761 1900 Fax +61 3 8761 1955 Website https://www.autoklene.com/msds/
Name Address 1/83 Merrindale Drive VIC Croydon 3136 Australia Telephone +61 3 8761 1900 Fax +61 3 8761 1955 Website https://www.autoklene.com/msds/
Telephone +61 3 8761 1900 Fax +61 3 8761 1955 Website https://www.autoklene.com/msds/
Fax +61 3 8761 1955 Website https://www.autoklene.com/msds/
Website https://www.autoklene.com/msds/
Fig. 10 Not A citable
Email Not Available
mergency telephone number
Association / Not Available Organisation
Emergency telephone numbers 131 126 (Poisons Information Centre)
Other emergency telephone numbers 0800 764 766 (New Zealand Poisons Information Centre)

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Classified as Dangerous Goods for transport purposes.

CHEMWATCH HAZARD RATINGS

	Min Max	(
Flammability	0	
Toxicit	3	0 = Minimum
Podu	4	1 = Low 2 = Moderate
Reactivity	1	3 = High
Chronic	3	4 = Extreme

[1] Classification	Metal Corrosion Category 1, Acute Toxicity (Oral) Category 3, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1, Carcinogenicity Category 1A, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation)			
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI			
Determined by Chemwatch using GHS/HSNO criteria	6.1C (oral), 6.1D (inhalation), 6.7A, 6.9 (respiratory), 8.1A, 8.2A, 8.3A			
abel elements				
H301	Toxic if swallowed.			
H332	Harmful if inhaled.			
H314	Causes severe skin burns and eye damage.			
H350	May cause cancer.			
H335	May cause respiratory irritation.			
recautionary statement(s) P	revention			
P201	Obtain special instructions before use.			
P260	Do not breathe dust/fume/gas/mist/vapours/spray.			
P270	Do not eat, drink or smoke when using this product.			
P271	Use only outdoors or in a well-ventilated area.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
P281	Use personal protective equipment as required.			
P234	Keep only in original container.			
Precautionary statement(s) R	esponse			
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.			
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.			
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.			

Version No: **2.1.1.1** Print Date: **08/02/2017**

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P363	Wash contaminated clothing before reuse.	
P390	Absorb spillage to prevent material damage.	
Precautionary statement(s) \$	Storage	
P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
Precautionary statement(s) [Disposal	
P501	Dispose of contents/container in accordance with local regulations.	
SECTION 2 COMPOSITIO	NI / INFORMATION ON INCREDIENTS	

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1341-49-7	<10	ammonium bifluoride
7664-93-9	<10	sulfuric acid
	balance	Ingredients determined not to be hazardous

SECTION 4 FIRST AID MEASURES

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Description of first aid measures

escription of mist aid meas	Nation
Eye Contact	If this product comes in contact with the eyes: ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If there is evidence of severe skin irritation or skin burns: ► Avoid further contact. Immediately remove contaminated clothing, including footwear. ► Flush skin under running water for 15 minutes. ► Avoiding contamination of the hands, massage calcium gluconate gel into affected areas, pay particular attention to creases in skin. ► Contact the Poisons Information Centre. ► Continue gel application for at least 15 minutes after burning sensation ceases. ► If pain recurs, repeat application of calcium gluconate gel or apply every 20 minutes. ► If no gel is available, continue washing for at least 15 minutes, using soap if available. If patient is conscious, give six calcium gluconate o calcium carbonate tablets in water by mouth. ► Transport to hospital, or doctor, urgently.
Inhalation	 ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if
	 ▶ necessary. ▶ Transport to hospital, or doctor, without delay. For massive exposures: ▶ If dusts, vapours, aerosols, fumes or combustion products are inhaled, remove from contaminated area. ▶ Lay patient down. ▶ Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. ▶ Perform CPR if necessary. ▶ If victim is conscious, give six calcium gluconate or calcium carbonate tablets in water by mouth. ▶ Transport to hospital, or doctor, urgently.

Version No. 2.1.1.1 Print Date: 08/02/2017

- ▶ For advice, contact a Poisons Information Centre or a doctor at once.
 - ▶ Urgent hospital treatment is likely to be needed.
 - ▶ If swallowed do **NOT** induce vomiting.
 - ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 - ▶ Observe the patient carefully.

▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. • Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Following acute or short term repeated exposure to hydrofluoric acid:

Ingestion

- ▶ Subcutaneous injections of Calcium Gluconate may be necessary around the burnt area. Continued application of Calcium Gluconate Gel or subcutaneous Calcium Gluconate should then continue for 3-4 days at a frequency of 4-6 times per day. If a "burning" sensation recurs, apply more frequently.
- Where serum calcium is low, or clinical, or ECG signs of hypocalcaemia develop, infusions of calcium gluconate, or if less serious, oral Sandocal, should be given. Hydrocortisone 500 mg in a four to six hourly infusion may help.
- Antibiotics should not be given as a routine, but only when indicated.
- ▶ Eye contact pain may be excruciating and 2-3 drops of 0.05% pentocaine hydrochloride may be instilled, followed by further irrigation

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Sampling Time Comments Determinant During or end of shift B, NS, SQ 1. Methaemoglobin in blood 1.5% of haemoglobin

B: Background levels occur in specimens collected from subjects NOT exposed.

NS: Non-specific determinant: Also seen after exposure to other materials

SQ: Semi-quantitative determinant - Interpretation may be ambiguous; should be used as a screening test or confirmatory test.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result Advice for firefighters ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus.

Fire Fighting

- ▶ Prevent, by any means available, spillage from entering drains or water course.
- ▶ Use fire fighting procedures suitable for surrounding area.
- ▶ Do not approach containers suspected to be hot.
- ▶ Cool fire exposed containers with water spray from a protected location.
- ▶ If safe to do so, remove containers from path of fire.

Non combustible.

- ▶ Not considered to be a significant fire risk.
- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ May emit corrosive, poisonous fumes. May emit acrid smoke.

Decomposition may produce toxic fumes of:

Fire/Explosion Hazard

carbon dioxide (CO2)

hydrogen fluoride

nitrogen oxides (NOx)

sulfur oxides (SOx)

other pyrolysis products typical of burning organic material.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Version No. 2.1.1.1 Print Date: 08/02/2017

Methods and material for containment and cleaning up

▶ Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. • Check regularly for spills and leaks.

▶ Clean up all spills immediately.

Avoid breathing vapours and contact with skin and eyes. Minor Spills

▶ Control personal contact with the substance, by using protective equipment. ▶

Contain and absorb spill with sand, earth, inert material or vermiculite.

▶ Place in a suitable, labelled container for waste disposal.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

▶ May be violently or explosively reactive.

▶ Wear full body protective clothing with breathing apparatus.

▶ Prevent, by any means available, spillage from entering drains or water course. ▶

Consider evacuation (or protect in place).

▶ Stop leak if safe to do so. Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Major Spills

Precautions for safe handling

▶ DO NOT allow clothing wet with material to stay in contact with skin

- ▶ Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area. Safe handling
 - - ▶ WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material
 - Avoid smoking, naked lights or ignition sources.
 - ▶ Avoid contact with incompatible materials.
 - ▶ When handling, DO NOT eat, drink or smoke

Other information

Store in original containers.

- ▶ Keep containers securely sealed. ▶ Store in a cool, dry, well-ventilated area.
- ▶ Store away from incompatible materials and foodstuff containers.
- ▶ Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

▶ DO NOT use aluminium or galvanised

containers ▶ Check regularly for spills and leaks

- ▶ Lined metal can, lined metal pail/ can,
- ▶ Plastic pail.
- ▶ Polyliner drum.
- ▶ Packing as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

For low viscosity materials

Suitable container

- ▶ Drums and jerricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):
- ▶ Removable head packaging; ▶
- Cans with friction closures and
- low pressure tubes and cartridges

may be used.

Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic

Ammonium bifluoride:

- ▶ reacts with water forming a weak solution of hydrofluoric acid ▶
- reacts violently with bases releasing ammonia gas
- ▶ attacks glass, cement and most metals in the presence of moisture ▶ upon contact with moisture and meal may release flammable hydrogen gas which may collect in confined spaces -a void aluminium, nickel or steel containers > when heated to decomposition emits toxic and corrosive fumes of ammonia, hydrogen fluoride and nitric oxides

Storage incompatibility

- Contact with acids produces toxic fumes
- ▶ Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.

Sulfuric acid :

- ▶ is a strong oxidiser i
- reacts with water or steam
- ▶ reacts violently with many substances including reducing agents, combustible materials, organic substances, alkalis, ammonium tetraperoxochromate, aniline, 1,2-ethanediamine, ethanolamine, isoprene, mesityl oxide, endo--norbanecarboxylic acid ethyl ester, perchlorates, sodium carbonate, zinc chlorate
- reacts, possibly causing ignition or explosion, with many substances, including non-oxidising mineral acids, organic acids, bases, reducing
- anhydride, acetone cyanohydrin, acetonitrile, acrolein, acrylates, acrylonitrile, alcohols, aldehydes, alkylene oxides, allyl alcohol, allyl chloride, substituted allyls, 2-aminoethanol, ammonium hydroxide, bromine pentafluoride, n-butyraldehyde, caprolactam solution, carbides, caesium acetylene carbide, chlorine trifluoride, chlorates, chlorosulfonic acid, cresols, cuprous nitride, diisobutylene, ethylene cyanohydrin, ethylene

Version No: **2.1.1.1** Print Date: **08/02/2017**

diamine, ethylene glycol, ethyleneimine, fulminates, glycols, hydrochloric acid, iodine heptafluoride, iron, isocyanates, ketones, lithium silicide, mercuric nitride, 2-methyllactonitrile, powdered metals, nitric acid, p-nitrotoluene, pentasilver trihydroxydiaminophosphate, perchloric acid, phenols, phosphorus, picrates, potassium chlorate, potassium permanganate, beta-propiolactone, propylene oxide, pyridine, rubidium acetylene, silver permanganate, sodium, sodium chlorate, sodium hydroxide, styrene monomer, zinc phosphide

increases the explosive sensitivity of nitromethane incompatible with 2-amino-5-nitrothiazole, 2-aminothiazole, ammonia, aliphatic amines, alkanolamines, amides, organic anhydrides, isocyanate, vinyl acetate,

alkylene oxides, epichlorohydrin attacks some

plastics, rubber and coatings reacts with metals to

produce flammable hydrogen gas

Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	ammonium bifluoride	Fluorides, as F	2.5 mg/m3	Not Available	Not Available	(bio) - Exposure can also be estimated by biological monitoring.
New Zealand Workplace Exposure Standards (WES)	sulfuric acid	Sulphuric acid	1 mg/m3	Not Available	Not Available	6.7A - Confirmed carcinogen

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ammonium bifluoride	Ammonium hydrogen fluoride; (Ammonium bifluoride)	11 mg/m3	130 mg/m3	750 mg/m3
sulfuric acid	Sulfuric acid	Not Available	Not Available	Not Available
Ingredient	Original IDLH	Revised IDLH		
ammonium bifluoride	500 mg/m3	250 mg/m3		
sulfuric acid	80 mg/m3	15 mg/m3		

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Personal protection











Eye and face protection

Hands/feet

protection

- ▶ Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.
- ▶ Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- ▶ Alternatively a gas mask may replace splash goggles and face shields.
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

Skin protection

See Hand protection below

- ▶ Elbow length PVC gloves
- ▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Wear safety footwear.

Body protection

See Other protection below

Version No. 2.1.1.1

▶ Overalls.

- ▶ PVC Apron.
- ▶ PVC protective suit may be required if exposure severe.
- ▶ Evewash unit.
- Ensure there is ready access to a safety shower.

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

Other protection

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

Auto Klene CODE RED

Material	СРІ
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
PE	С
PVC	С
SARANEX-23	С

CPI - Chemwatch Performance Index

Information on basic physical and chemical properties

Appearance

Flammability

Upper Explosive Limit

(%)

Lower Explosive Limit

(%)

Not Applicable

Not Applicable

Not Applicable

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation.

* Where the glove is to be used on a short term, casual or infrequent basis, factors

Thermal hazards Not Available

Recommended material(s)

GLOVE SELECTION INDEX

such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Liquid; mixes with water.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Issue Date: 26/01/2017

Print Date: 08/02/2017

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AE-AUS P2	-	AE-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AE-AUS / Class 1 P2	-
up to 100 x ES	-	AE-2 P2	AE-PAPR-2 P2 ^

^{^ -} Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G =

Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the $% \left(1\right) =\left(1\right) \left(1\right$ respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Respiratory protection

Oxidising

properties Surface Tension (dyn/cm

Volatile Component (%vol)

or mN/m)

Not Available

Not Available

Not Available

Type AE-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI

Physical state	Liquid	Relative density (Water = 1)	0.9
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

Version No: **2.1.1.1** Print Date: **08/02/2017**

Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Contact with alkaline material liberates heat ► Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

formation on toxic	cological effects	
Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the mate The material can cause respiratory irritation in some persons. The body	• •
Ingestion	of the individual.	nimal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious uth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may als
Skin Contact	through the skin and cause death of soft tissue and erode bone. Healing Open cuts, abraded or irritated skin should not be exposed to this mater Contact of the skin with liquid hydrofluoric acid (hydrogen fluoride) may blue-gray discoloration, and necrosis may occur. Solutions of hydrofluor	
Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitive	vity to light and burns. Mild burns of the epithelia generally recover rapidly and completely.
Chronic	often occurs. Long-term exposure to respiratory irritants may result in disease of the a Studies show that inhaling this substance for over a long period (e.g. in Substance accumulation, in the human body, may occur and may cause Strong inorganic acid mists containing sulfuric acid can cause cancer.	an occupational setting) may increase the risk of cancer. e some concern following repeated or long-term occupational exposure. es signs of joint pain and stiffness, tooth discolouration, nausea and vomiting, loss of appetite, diarr
Auto Klene CODE RED	TOXICITY Not Available	IRRITATION Not Available
ammonium bifluoride	тохісіту	IRRITATION
	Inhalation (rat) LC50: 1276 ppm/1h ^[2] Oral (rat) LD50: 130 mg/kg ^{1]}	Eye (-): corrosive* Skin (-): corrosive*

Chemwatch: **5240-43** Version No: 2.1.1.1

Issue Date: 26/01/2017 Print Date: 08/02/2017

	TOXIO	CITY	IRRITATION		
sulfuric acid	Inhala	tion (guinea pig) LC50: 0.018 mg/L/8hr	Eye (rabbit): 1.38 mg SEVERE		
	Inhala	tion (mouse) LC50: 0.32 mg/L/2hr	Eye (rabbit): 5 mg/30sec SEVE	RE	
	Inhala	tion (rat) LC50: 0.51 mg/L/2nr			
	,	rat) LD50: 2140 mg/kg []]			
	Legend: 1	Value obtained from Europe ECHA Registered Substan specified data extracted from RTECS - Register of Tox		m manufacturer's SDS. Unless otherwise	
		for acid mists			
		for acid mists, aerosols, vapours Data from assays for genotoxic activity in vitro suggest the from the respiratory tract have not been examined in this			
		inhaled acidic mists, just as mucous plays an important role in protecting the gasti genotoxic events in vivo in the respiratory system, compa		· ·	
AMMONIUM BIFLI	UORIDE	fasting or nocturnal conditions, and with the human urinary bladder	, in which the pH of urine can range from	<5 to > 7 and normally averages 6.2. Furthermore,	
		exposures to low pH in vivo differ from exposures in vitro	in that, in vivo, only a portion of the cell s		
		that perturbation of intracellular homeostasis may be maintained more readily than in vitro. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.			
		The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of			
		vesicles, scaling and thickening of the skin.			
SULFU	RIC ACID	WARNING: For inhalation exposure ONLY: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS Occupational exposures to strong inorganic acid mists of sulfuric acid:			
		Asthma-like symptoms may continue for months or ever known as reactive airways dysfunction syndrome (RADS for the diagnosis		,	
	AMMONIUM BIFLUORIDE & SULFURIC ACID SULFURIC ACID The concentration of and duration of exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of			try, with the presence of moderate to severe flammation, without eosinophilia, have also been s an infrequent disorder with rates related to the	
		exposure due to high concentrations of irritating substandisorder is characterised by dyspnea, cough and mucus		pletely reversible after exposure ceases. The	
Acute T	oxicity	~	Carcinogenicity	~	
Skin Irritation/C	orrosion	~	Reproductivity		
Serio Damage/Irr	us Eye ritation	~	STOT - Single Exposure	~	
Respiratory o	or Skin isation	0	STOT - Repeated Exposure	0	
Mutag	jenicity	0	Aspiration Hazard		
			Legend: X	- Data available but does not fill the criteria for classification - Data available to make classification	

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
ammonium bifluoride	LC50	96	Fish	0.068mg/L	2
ammonium bifluoride	EC50	96	Crustacea	26-48mg/L	2
ammonium bifluoride	NOEC	744	Fish	<0.048mg/L	2
sulfuric acid	LC50	96	Fish	=8mg/L	1
sulfuric acid	EC50	48	Crustacea	=42.5mg/L	1
sulfuric acid	EC50	240	Algae or other aquatic plants	2.5000mg/L	4
sulfuric acid	NOEC	7200	Fish	0.13mg/L	2

Data available to make classification
 Data Not Available to make classification

 Chemwatch: 5240-43
 Page 10 of 15
 Issue Date: 26/01/2017

 Version No: 2.1.1.1
 Print Date: 08/02/2017

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12
Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan)
Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

For Fluorides: Small amounts of fluoride have beneficial effects however; excessive intake over long periods may cause dental and/or skeletal fluorosis. Fluorides are absorbed by humans following inhalation of workplace and ambient air that has been contaminated, ingestion of drinking water and foods and dermal contact. Populations living in areas with high fluoride levels in groundwater

may be exposed to higher levels of fluorides in their drinking water or in beverages prepared with the water. Among these populations, outdoor labourers, people living in hot climates, and people with excessive thirst will generally have the greatest daily intake of fluorides because they consume greater amounts of water.

Atmospheric Fate: Both hydrogen fluoride and particulate fluorides will be transported in the atmosphere and deposited on land or water by wet and dry deposition. Non-volatile inorganic fluoride particulates are removed from the atmosphere via condensation or nucleation processes. Fluorides adsorbed on particulate matter in the atmosphere are generally stable and are not readily hydrolyzed, although they may be degraded by radiation if they persist in the atmosphere. For Sulfuric Acid:

Environmental Fate: Large discharges of sulfuric acid may contribute to the acidification of water and be fatal to aquatic life and soil micro-organisms, and may contribute to the acidification of effluent treatment systems and injure sewage treatment organisms. The substance will react violently with a variety of other chemicals, as well as water. Atmospheric Fate: Sulfuric acid is removed from the air by dry/wet deposition. In the stratosphere, sulfuric acid aerosols have lifetimes of about 14 and 2.4 days, at altitudes of 15 and 20 km, respectively. At cloud level, the residence time is about 6 days, with shorter residence times in surface air. The substance will react with atmospheric water, (hygroscopic). The substance is a strong oxidizer, (reacts with oxygen), and is highly corrosive to stainless steel.

Prevent, by any means available, spillage from entering drains or water

courses. DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

- Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and SDS and observe all notices pertaining to the product.
 Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some

Product / Packaging disposal

areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
 - Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type.

possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be appl. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered
- first. Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible
- material)

Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.

Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

Chemwatch: **5240-43**Version No: **2.1.1.1**

SECTION 14 TRANSPORT INFORMATION

Labels Required		
	8 6	
Marine Pollutant	NO	
HAZCHEM	2X	
Land transport (UN)		
UN number	2817	
UN proper shipping name	AMMONIUM HYDROGEN- DIFLUORIDE SOLUTION	
Transport hazard class(es)	Class 8 Subrisk 6.1	
Packing group	Ш	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions Not Applicable Limited quantity 1 L	
Air transport (ICAO-IATA / DO	GR)	
UN number	2817	
UN proper shipping name	Ammonium hydrogendifluoride solution	
Transport hazard class(es)	ICAO/IATA Class 8 ICAO / IATA Subrisk 6.1 ERG Code 8P	
Packing group	11	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instruction Passenger and Cargo Limited Maximum Qty / Pack	A3A803 855 30 L 851 1 L nsY840 0.5 L
Sea transport (IMDG-Code / 0	GGVSee)	
UN number	2817	
UN proper shipping name	AMMONIUM HYDROGENDIFLUORIDE SOLUTION	
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk 6.1	
Packing group	Ш	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number F-A, S-B Special provisions Not Applicable Limited Quantities 1 L	

Issue Date: **26/01/2017**Print Date: **08/02/2017**

Version No: 2.1.1.1 Print Date: 08/02/2017

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR100425	Pharmaceutical Active Ingredients Group Standard 2010

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Inventory of Chemicals (NZIoC)

AMMONIUM BIFLUORIDE(1341-49-7) IS FOUND ON THE FOLLOWING

REGULATORY LISTS

New Zealand Workplace Exposure Standards (WES) New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

SULFURIC ACID(7664-93-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List

Passenger and Cargo Aircraft

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities
6.1A, 6.1B, 6.1C (except for propellant powders of classes 1.1C (UN 0160) and 1.3C (UN 0161)	Any quantity
6.7A	10 kg or more, if solid 10 L or more, if liquid
8.2A	Any quantity

Refer Group Standards for further information

Tracking Requirements

Subject to Hazardous Substances (Tracking) Regulation 2001

- Refer to the regulation for more information

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Υ
Canada - NDSL	N (ammonium bifluoride; sulfuric acid)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	Υ
Korea - KECI	Υ
New Zealand - NZIoC	Υ

Auto	Klene	Acid	Klene	WA			
Page 13 of 15							

Chemwatch: 5240-43		Page 13 of 15 Issue Date: 26	Issue Date: 26/01/2017	
Ver	sion No: 2.1.1.1	Print Date: 08	3/02/2017	
	Philippines - PICCS	Y		
	USA - TSCA	Υ		
	Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets,)	

SECTION 16 OTHER INFORMATION

Chemwatch: 5240-43 Page 14 of 15 Issue Date: 26/01/2017

Auto Klene CODE RED

Version No: 2.1.1.1

Print Date: 08/02/2017

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Chemwatch: **5240-43** Page **15** of **15** Issue Date: **26/01/2017**

Version No: 2.1.1.1

Print Date: 08/02/2017