

Datasheet

Fujitsu ETERNUS DX80 S2 Disk Storage System

The Flexible Data Safe for Dynamic Infrastructures.



ETERNUS DX S2 DISK STORAGE SYSTEMS

Fujitsu's second generation of ETERNUS DX disk storage systems, ETERNUS DX S2, are The Flexible Data Safe for Dynamic Infrastructures. Enterprise-proven capabilities protect data assets across all types of IT infrastructure. Redundant components, RAID protection and build-in data protection provide the highest system reliability to ensure business continuity is maintained.

ETERNUS DX S2 models are comprehensive disk storage platforms with superior scalability to address the demands of intensive data growth and highest performance. Free choice of modular disk storage and state-of-the-art connectivity across the entire model range delivers maximum configuration flexibility allowing choice in performance and TCO. Data-in-place upgrade options are also available throughout the system's lifecycle to ensure maximum investment protection.

The unified ETERNUS SF storage management software enables single point administration, easy data protection and efficient operation across the entire ETERNUS DX range. In virtualized IT environments in particular, ETERNUS SF perfectly integrates the powerful ETERNUS DX disk storage with minimal administration effort.

ETERNUS DX80 S2

The ETERNUS DX80 S2 with Intel® Xeon® processors is a reliable and flexible disk storage system for medium-sized IT environments. It offers an outstanding price/performance ratio and is easy to manage, thus reducing operational effort. It provides remarkable scalability with storage capacity of up to 360 TB, thus offering enough headroom for future growth. The flexible support for different network connectivity and disk types (SAS, Nearline SAS and SSD) provides a choice between cost and performance optimization. The ETERNUS DX80 offers Thin Provisioning allowing a more cost-efficient use of storage capacity right from the start. Data-in-place upgrades lead seamlessly to the next higher ETERNUS DX system, thus ensuring flexibility and investment protection. The enclosed ETERNUS SF Express software reduces administration work and provides data safety functionality.



**Green
Policy
Innovation**

Green Product

This product cleared our company's original evaluation standard which followed global environmental measures.

Features and benefits

Main features	Benefits
Data center functionality already in the Entry class	<ul style="list-style-type: none">■ Flexible configuration of drives and connectivity; enables flexible balancing of performance, capacity and costs■ Ensures data safety and high availability through comprehensive features like encryption, redundancy, copy functions and snapshots■ Efficient operations through technologies such as Tiering, Thin Provisioning and Eco-mode
Richly featured management suite at no extra costs	<ul style="list-style-type: none">■ Free of charge ETERNUS SF Express Storage Management■ Snapshot functionality already included■ Easy and efficient operation
Unique and consistent family concept	<ul style="list-style-type: none">■ Seamless and fully compatible product family of disk storage systems with uniform system components and unified management software■ Family concept reduces operations, maintenance, migration and training efforts as well as costs■ Migration path to the next bigger model

Technical details

General Specification		2.5" Base Model		3.5" Base Model		
		Single Controller	Dual Controller	Single Controller	Dual Controller	
Supported RAID Levels		0, 1, 1+0, 5, 5+0, 6				
Host Interfaces		Fibre Channel (16/8/4/2 Gbit/s) FCoE (10 Gbit/s) iSCSI (10 Gbit/s) or iSCSI (1 Gbit/s) SAS (6/3 Gbit/s)				
Number of controllers		1	2	1	2	
Number of host interfaces		2/4 ports	4/8 ports	2/4 ports	4/8 ports	
- Notes		Mixed configurations are possible.				
Number of hosts		Max. 1,024				
Cache memory capacity		2 GB	4 GB	2 GB	4 GB	
Number of drive enclosures		Max. 4 (2.5") / Max. 9 (3.5")				
Number of drives		Max. 120				
Storage capacity		Physical capacity Max. 360.0 TB Logical capacity Max. 267.0 TB				
Drives	3.5-inch	SAS disk drives				
		Nearline SAS disk drives				
		SSD (Solid State Drives)				
- Notes		3.5" drives are available only for 3.5" drive enclosures.				
2.5-inch	SAS Non-Encrypting drives		900 GB/600 GB/450 GB/300 GB (10,000 rpm), 300GB (15,000 rpm)			
	SAS Self-Encrypting drives		900 GB/600 GB/450 GB/300 GB (10,000 rpm)			
	Nearline SAS disk drives		1 TB (7,200 rpm)			
	SSD (Solid State Drives)		800 GB/400 GB/200 GB/100 GB			
- Notes		2.5" drives are available only for 2.5" drive enclosures.				
Drive interface		Serial Attached SCSI (6 Gbit/s)				
Back-End Disk Connectivity		1 pair of four-lane x 6 Gbit/s Serial Attached SCSI buses (SAS 2.0 wide)				
Redundancies	RAID Controller		No	Yes	No	Yes
	Fan		Yes	Yes	Yes	Yes
	Power Supply		Yes	Yes	Yes	Yes
Number of LUN		Max. 2,048				
LUN capacity		Max. 128 TB				
Number of Snapshots	Standard (built-in)		8			
	Maximum (option)		1,024			
- Note		Local Copy License must be purchased to maximize the number of Snapshots				
Number of copy generations		256				
Remote Copy feature		No				

Installation Specification		2.5" Base Model		3.5" Base Model	
Dimensions (Standard) (W x D x H)	Controller enclosure (CE)		CE: 482 × 645 × 88 mm (2U)	CE: 482 × 670 × 88 mm (2U)	
	Drive enclosure (DE)		DE: 482 × 540 × 88 mm (2U)	DE: 482 × 555 × 88 mm (2U)	
Service Area	Front		800 mm (31.5 inch) or more		
	Rear		800 mm (31.5 inch) or more		
Maximum Weight			175 kg (35 kg per single enclosure)	350 kg (35 kg per single enclosure)	
			385 lb (77 lb per single enclosure)	770 lb (77 lb per single enclosure)	

Installation Specification (Continued)		2.5" Base Model	3.5" Base Model	
Power	Voltage	AC 100 – 120 V / AC 200 – 240 V		
	Phase	Single		
	Frequency	50 Hz / 60 Hz		
Maximum Power Consumption	AC 100 - 120V	CE	630 W (640 VA)	620 W (630 VA)
		DE	570 W (580 VA)	550 W (560 VA)
		Max	2,910 W (CE+2.5"DEx4) 2,960 VA (CE+2.5"DEx4)	5,570 W (CE+3.5"DEx9) 5,670 VA (CE+3.5"DEx9)
	AC 200 - 240V	CE	630 W (640 VA)	610 W (620 VA)
		DE	570 W (580 VA)	550 W (560 VA)
		Max	2,910 W (CE+2.5"DEx4) 2,960 VA (CE+2.5"DEx4)	5,560 W (CE+3.5"DEx9) 5,660 VA (CE+3.5"DEx9)
Maximum Heat Generation	AC 100 - 120V	10,700 kJ/h (10,200 BTU/h)	20,300 kJ/h (19,300 BTU/h)	
	AC 200 - 240V	10,700 kJ/h (10,200 BTU/h)	20,200 kJ/h (19,200 BTU/h)	
Environmental Conditions	Temperature	10 – 40°C (Operating)		
		50 – 104°F (Operating)		
	Humidity	20 – 80% RH (Operating)		
Altitude		3,000 m (10,000 ft.)		
Operating environment		FTS 04230 Guideline for Data Center (installation locations)		
Operating environment link		http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe		

Management

Interfaces	Ethernet (1000 Base-T / 100 Base-TX / 10 Base-T)
Supported protocols	SNMP (version1, 2C, 3), SMI-S 1.4
Administration	Web-Environment, CLI (Command Line Interface), ETERNUS SF Express

Supported OS For ETERNUS SF Express

Operation Management Server	Microsoft® Windows Server®2008 Standard (32-bit) (64-bit) including R2
	Microsoft® Windows Server® 2008 Enterprise (32-bit) (64-bit) including R2
	Microsoft® Windows Server® 2008 Datacenter (32-bit) (64-bit) including R2
Operation Management Client	Microsoft® Windows® 7 Home Premium
	Microsoft® Windows® 7 Professional
	Microsoft® Windows® 7 Ultimate
	Windows Vista® Home Basic
	Windows Vista® Home Premium
	Windows Vista® Business
	Windows Vista® Enterprise
	Windows Vista® Ultimate
	Windows® XP Home Edition
	Windows® XP Professional
	Microsoft® Windows Server®2008 Standard (32-bit) (64-bit)
	Microsoft® Windows Server® 2008 Enterprise (32-bit) (64-bit)
	Microsoft® Windows Server® 2008 Datacenter (32-bit) (64-bit)

Options

License	ETERNUS SF Local Copy License
---------	-------------------------------

Noise Emission	2.5" Base Model	3.5" Base Model
Sound Power Level (LWAd)		6.6 B
Sound Pressure Level (LpAm)		49 dB(A)
- Notes	measured with single enclosure according to ISO7779 and declared according to ISO9296	

Warranty

Global Base Warranty	3 years
----------------------	---------

Maintenance and Support Services

The perfect extension of the product specific base warranty for optimized operation.

Recommended Service: 24 x 7 Fujitsu support for enterprise class services.

Please check your specific service level with your FUJITSU sales organization or partner.

Supported configurations

A wide range of host operating systems, servers as well as applications is supported.

For a detailed support matrix check:

<http://www.fujitsu.com/global/services/computing/storage/eternus/products/diskstorage/dx-entry/supported-device/>

Compliance With Standards

Product safety	UL60950-1, CSA-C22.2 No. 60950-1, EN60950-1, IEC60950-1, GOST-R
Electromagnetic Compatibility	CNS13438(C6357) Class A, FCC CFR47 part 15 Class A, ICES-003 Class A, EN55022 Class A, VCCI Class A, AS/NZS CISPR22 Class A
Electromagnetic Immunity	EN55024
CE certification	Electromagnetic Compatibility Directive 2004/108/EC Low Voltage Directive 2006/95/EC
Environmental compliance	RoHS-compliant (Restriction of hazardous substances) WEEE-compliant (Waste electrical and electronic equipment)
- Notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.

More information

Fujitsu platform solutions

In addition to Fujitsu ETERNUS DX, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure-as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing products

www.fujitsu.com/global/services/computing/
- PRIMERGY: Industry standard server
- SPARC Enterprise: UNIX server
- PRIMEQUEST: Mission-critical IA server
- ETERNUS: Storage system

Software

www.fujitsu.com/software/
- Interstage: Application infrastructure software
- Systemwalker: System management software

More information

Learn more about Fujitsu ETERNUS DX80 S2, please contact your Fujitsu sales representative, Fujitsu business partner, or visit our website.
www.fujitsu.com/eternus/

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at:
www.fujitsu.com/global/about/environment/



Copyright

© Copyright 2012 Fujitsu Limited. Fujitsu, the Fujitsu logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners.

Disclaimer

Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Limited
Website: www.fujitsu.com/eternus/
2013-01-17 WW-EN