Jandel Engineering Limited



Cartridge probe with 6-way connector (KLA/Tencor)

Jandel Engineering Limited manufactures the cartridge with 6-way connector probe head to be compatible with systems manufactured by KLA/Tencor (formerly Prometrix).

All Jandel probes are built to a high level of mechanical accuracy. Specifications for radii, spacing and planarity are verified by video inspection system and optical interferometer. Loads are verified by electronic force gauge. Each probe has upper and lower jeweled needle guides.

The probe manufactured for CDE tools is very similar, however the probes are not inter-changeable and great care should be taken, especially if both systems are in use on site. CDE compatible probe heads have a distinctive black nosepiece.

| Probe spacing | 0.500mm, 0.635mm, 1.00mm, 1.27mm, 1.591mm (needle to needle) |
|--------------------|--|
| Tolerance | +/- 10 microns |
| Arrangement | Linear or square array |
| Needles | Tungsten carbide 0.4mm diameter (0.3mm diameter for close spacing) |
| Needle option | 50% Osmium alloy tips are available |
| Radii | 12.5, 25, 40, 100, 150, 200, 300, 500 microns |
| Retraction to pad | 0.5 mm |
| Planarity | +/- 0.025mm or better |
| Loads | Fixed between 10g and 250g |
| Electrical leakage | 10 ¹³ ohms resistance between needles at 500 volts |

If you require any further information on the Jandel Cartridge probe with 6-way connector please do not hesitate to contact us using the details below