

FLOOD LIGHT




INNOVATIVE LED LIGHTING

CLFA/B-U Series

by PolyBrite International, Inc.



The CLFA/B-U fixture is a versatile LED solution with full 360 degree rotation, providing exacting illumination performance, available in a wide range of power levels to suit your requirements.



FEATURES & BENEFITS

- Modular design allows for easy installation, replacement and maintenance. This design also creates a chimney effect which provides exceptional thermal management.
 - Corrosion resistant polyester powder painted 100µm thickness.
 - Meets a 1000-hour salt spray certification per ASTM B117/ ISO 9227:2012.
 - Over 20 optical lenses are available for virtually any application.
 - Extremely flexible with full 360 degree rotation.
 - Interchangeable with the other CLFAB Series with a bracket change.
 - Multiple smart lighting control options are available, e.g. photocell, motion sensor, DALI, 1-10V.
 - UL/CUL/ DLC/ LM79/ SAA/ ENEC/ CB/ CE/ EFP/ RgHS / IK08
- Not all products are qualified on the DLC QPL. To view our DLC qualified products please consult the DLC Qualified Product List at www.designlights.org

TECHNICAL PARAMETERS

Power	30-320W
Input	120-277VAC or 220-240VAC or 347-480VAC
PF	> 0.95
THD	< 20%
L70/L90	> 200,000H/ > 60,000H
Operating Temperature	-40°C ~ + 60°C
Efficacy	120-160lm/W
ANSI CCT	3000K/4000K/5000K/5700K
Min CRI	70* or 80 or 90
IP Rating	IP67
SPD	Optional
DALI	Optional
1-10V	Optional
Photocell	Optional
Smart Control	Optional
Optic (IESNA)	Type II, Type III, Type IV, Type V
Color Options	Grey/Black/Bronze/White

* Standard

ORDERING INFORMATION

Example : CLFA30-U-T2M-50K-GR-03

MODEL (Nominal Power)	MOUNTING		OPTIC LENS	CCT (ANSI)	OPTIONAL COLOR	LIGHTING CONTROL	ACCESSORY INFO
	120-277VAC or 220-240VAC (30W/module)	120-277VAC or 220-240VAC (40W/module)					
CLFA30	CLFB40	T2M	30K	BK	00	Bird Spike	
CLFA60	CLFB80	T3M	40K	GR	Not required		
CLFA90	CLFB120	T3L	50K	BZ	01	10KA/20KA Surge Protection Device	
CLFA120	CLFB160	T4S	57K	WH	Photocell		
CLFA150	CLFB200	T4M			02	Back Light Shield	
CLFA180	CLFB240	T5U			03	Safety Cable	
CLFA210	CLFB280	T5V			Photocell +		
CLFA240	CLFB320	T5W			Motion Sensor		
CLFA270		T5S			04		
CLFA300		T5M			04		
		T5L			DALI		
		T5X			05		
		T5D			1-10V dimming		

* DALI & Motion sensor unavailable

★ Regularly stocked item

UV-06012018