

WORK WELL MATS Industrial Matting

DURA-TRED

CODE	SIZE MM	COLOUR
4206-1527	900 x 1520	Black/Yellow border
4206-2527	900 x 18300	Black/Yellow border

- Checker-plate pattern gives great visual appearance and offers an ultimate anti-slip surface.
- PVC top surface bonded to high density foam base.
- Slight gradient safety bevelled edges along long sides of mat.
- Aerated Foam provides a soft but firm footing that gives increased performance to the user.
- Oil, grease and chemical resistant.
- 16 mm overall thickness.
- Available as a continuous roll up to 18.3m long.



SOFT-STEP

CODE	SIZE MM	COLOUR
4007 1507	910 x 1520	Black
4207-1527	7.0 X 1520	D. G.C.
4207-1627	910 x 18300	Black
4207-2527	910 x 1520	Black/Yellow border
4207-2627	910 x 18300	Black/Yellow border

- Light/medium duty anti-fatigue matting for use in dry areas.
- Cushioned foam PVC construction, giving excellent anti-fatigue properties.
- Ribbed surface for good anti-slip protection.
- Insulates your feet against cold concrete floors.
- Cleans easily with mop, broom or hose.
- Optional static dissipative material makes Soft Step ideal for electronic or hazardous areas, and dry standing environments.



E: sales@wwmuk.uk W: www.wwmuk.uk

Thatchems Farm, Williamscot, Banbury, OX17 1AR

We also offer: Custom Shapes and Sizes On-site analysis and reports **Measuring and fitting service** Wide range of standard sizes available

UK AND IRELAND COVERAGE

Tel: 0845 658 8340 Fax: 0845 017 1352