







**Developed for heavy-duty contract and domestic use, series 4500 provides strength and multi-channel versatility for most curtain applications.** With 2 and 3 channel profiles in the series, curtain overlaps can be created using the entire track length. Profiles 4550 and 4560, designed for incorporation within suspended ceilings, provide flush mounting and concealed fixing.

Standard colour: White RAL 9010. Special colours on request.

## 




ceiling fixing 4540 using 4514-WD fixing screw with white cover cap



•		
+		a [mm]
3.5	4515-07.5	75
	4515-10	100
	4515-15	150

wall fixing 4520 with extension bracket 4515-10



fixing 4560 in suspended ceiling with 4555-SH



(bracket fixing guide)

4520

4530 ----

.5 mm

0.5 mm

8

4540 -

4550 ----

rail deflection

1.5 mi

[ka]

[cm]

140

120

100 distance

80

60

40

[cm]

260

220

180

60


dista 140

oracke. 100

curtain weight

bracket

curtain weight





## **Specification Guide**

#### Material:

Aluminium 606035-T6-F22. (Higher specification than DIN 1725). Shape and size tolerances are in accordance with DIN 17615. White RAL 9010 powder coated in accordance with the Qualicoat standard. Special colours available on request.

Profile weight 4520: 373 g/m. Profile weight 4530: 733 g/m. Profile weight 4540: 665 g/m.

Profile weight 4550: 691 g/m. Profile weight 4560: 853 g/m.

#### Accessories:

Gliders 4010 at 10 - 16 per metre and end stops 4001 at 4 or 6 per length.

#### Installation:

Ceiling fixing with white screw 4514-W or screw 4514-WD with white cover cap.


Profiles 4520, 4530 and 4540 - face fixing using extension bracket 4515. Profiles 4550 and 4560 - fixing within suspended ceilings using adjustable suspension hanger 4555-SH.


Bracket distance in accordance with G-Standard or the following table.

	light	medium	heavy	(curtain)
4520	100	80	60	
4530	120	100	80	
4540	130	110	80	
4550	200	130	90	
4560	200	130	90	

# ty " annel The values of the 4560 equal those of the 4550. profiles.

### **Product examples**






Example of a 90° corner connector and multi channel profile.

# Components

Product design and specification changes reserved.



09/2003