

## Skylights for Roofs (FM Approval Class Number 4431)

### M74 DS

Solatube Models M74 DS, 750 DS, and 330 DS are Tubular Daylighting Devices (TDD) are round in shape, and consists of transparent roof-mounted skylight domes, curb mounted or self-flashing curb, reflective tube, and ceiling level diffuser assemblies that transfer sunlight to interior spaces.

Product	Listing Country	Diameter (in)	Diameter (mm)	Lid Type	Wind Uplift (psf)	Wind Uplift (kPa)	Spread of Flame Rating	Hail Rating	Certification Type
M74 DS	USA	28.5	724	Polycarbonate	195	9.3	Class A	SH	FM Approved

#### **Solatube Model M74 DS**

FM Approved Solatube SkyVault Series Model M74 DS Tubular Daylighting Device (TDD), is 28.5 in. (724 mm) diameter daylighting system equipped with transparent, UV and impact resistant Dome material with flashing base supporting dome and top of tube. The dome glazing material is Type DP, minimum 0.125 in. (3.2 mm) thickness, vacuum formed polycarbonate classified as CC1 material; UV inhibiting (100 percent UVC, 100 percent UVB and 98.8 percent of the range of UVA transmission).

<b>Company Name:</b>	Solatube International Inc
<b>Company Address:</b>	2210 Oak Ridge Way, Vista, California 92081, USA
<b>Company Website:</b>	<a href="http://www.solatube.com">http://www.solatube.com</a>
<b>New/Updated Product Listing:</b>	Yes
<b>Listing Country:</b>	United States of America
<b>Width (ft in):</b>	2'4.5"
<b>Width (m):</b>	724
<b>Length (ft in):</b>	
<b>Length (m):</b>	
<b>Lid Type:</b>	Polycarbonate
<b>Wind Uplift (psf):</b>	195
<b>Wind Uplift (kPa):</b>	9.3
<b>Spread of Flame Rating:</b>	Class A at 5 in 12
<b>Hail Rating:</b>	Severe Hail with 2.0 in. diameter ice balls
<b>Certification Type:</b>	FM Approved