









LED COB Surface Mounted Downlight SM-A Series

CE/RoHS/TUV/SAA certification


Picture	Item	Model.No	Technology Specification				Size Picture	(Lifud + CREE)
	LED Surface Mounted Downlight	SL-SM-A07	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>90lm/w		
			Power:	7W	Size:	Φ55*H120mm		
			LED Chips:	CREE 1pcs	Install:	Surface Mounted		
			CCT:	3000K / 4000K / 5000K	CRI:	>90		
			Beam Angle:	15° / 24° / 38°	IP:	20		
			PF:	0.55	Dim Type:	Triac / 0-10V / DALI		
			Driver:	JST	Driver Optional:	JST / BOKE / OSRAM		
						Packaging : 46*35*50cm		
						50Pcs/Ctn 27KG/Ctn		
	LED Surface Mounted Downlight	SL-SM-A12	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w		
			Power:	12W	Size:	Φ80*H160mm		
			LED Chips:	CREE 1pcs	Install:	Surface Mounted		
			CCT:	3000K / 4000K / 5000K	CRI:	>90		
			Beam Angle:	15° / 24° / 38°	IP:	20		
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI		
			Driver:	JST	Driver Optional:	JST / BOKE / OSRAM		
						Packaging : 46*35*50cm		
						50Pcs/Ctn 27KG/Ctn		
	LED Surface Mounted Downlight	SL-SM-A15	Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w		
			Power:	15W	Size:	Φ80*H160mm		
			LED Chips:	CREE 1pcs	Install:	Surface Mounted		
			CCT:	3000K / 4000K / 5000K	CRI:	>90		
			Beam Angle:	15° / 24° / 38°	IP:	20		
			PF:	0.95	Dim Type:	Triac / 0-10V / DALI		
			Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM		
						Packaging : 46*35*50cm		
						50Pcs/Ctn 27KG/Ctn		



LED
Surface
Mounted
Downlight

SL-SM-A18

Input Voltage:	220-240V AC 50/60Hz	Luminous Flux:	>100lm/w
Power:	18W	Size:	Φ80*H160mm
LED Chips:	CREE 1pcs	Install:	Surface Mounted
CCT:	3000K / 4000K / 5000K	CRI:	>90
Beam Angle:	15° / 24° / 38°	IP:	20
PF:	0.95	Dim Type:	Triac / 0-10V / DALI
Driver:	Lifud	Driver Optional:	JST / BOKE / OSRAM



Packaging : 46*35*50cm

50Pcs/Ctn 27KG/Ctn